

Clack®

WS1.25SD WS1.25SP





**WATER
SPECIALIST
CONTROL
VALVE**



Certified to NSF/ANSI 44 and NSF/ANSI/CAN 61 and 372.



shown with optional bypass

SD	SP	SP RECHARGING OPTIONS	
			
D Cell Battery Pack	AA Rechargeable Battery Pack	DC Power Supply	Solar Panel

- Solar panel or DC power supply recharges 6 "AA" re-chargeable Nickel Metal Hydride Batteries
- Can be programmed for automatic variable reserve, based on water usage history for high efficiency
- Solid state microprocessor with easy access front panel settings
- Service flow rate of 34 gpm, backwash 32 gpm
- Front panel display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (Totalizer)
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Fully adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining/slow rinse, second backwash, fast rinse, refill and downflow service
- Coin Cell Lithium battery back-up with 8 hour carry over of time of day
- Backwash and brining ability to 21" diameter tanks
- Downflow regeneration/Upflow regeneration
- Level VI 15-volt output DC power supply provides safe and easy installation
- Patented one piece expanding seal spacer stack assembly
- Patented linearly reciprocating piston operation
- Control valve design provides optimum service and backwash rates
- Post treated water regenerant refill
- Reliable and proven DC drive

Water Specialist 1.25" SD/SP Control Specifications

Inlet/Outlet Fittings.....	¾" to 1.5" NPS
Cycles	up to 6
Valve Material	Fiber Reinforced Composite
Regeneration	Downflow

FLOW RATES

Service @15 psi drop (includes meter, bypass, and 1.25" fitting kit).....	34 gpm
Backwash @ 25 psi drop (includes bypass)	32 gpm (1)
Cv Service	8.8
Cv Backwash	6.4

OPERATING PRESSURES

Minimum/Maximum	20 psi – 125 psi
-----------------------	------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° – 110° F
-----------------------	--------------

METER

Accuracy	± 5%
Flow Rate Range.....	0.25 – 34 gpm
Gallon Range.....	20 – 1,500,000 gallons
Totalizer	1000 - 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot.....	1.32" OD Pipe (1" NPS) or 32mm OD
Drain Line	¾" or 1" Male NPT
Brine Line	¾" or ½" OD Poly Tube Compression
Mounting Base.....	2 ½" - 8 NPSM
Height From Top Of Tank.....	7 ¾"
Weight	4.5 lbs.

BATTERY SPECIFICATIONS - 2 OPTIONS FOR OPERATION

- 6 AA nickel metal hydride batteries rechargeable for SP model
- 6 "D" cell alkaline batteries (**disposable when discharged**) for SD model - "D" batteries not included

CHARGING SPECIFICATIONS FOR SP MODEL- 2 OPTIONS FOR OPERATION

- Amorphous silicon solar panels capable of three tilt angles
- DC power supply with 15VDC output 500mA

TANK APPLICATIONS

Water Softener	6" – 21" diameter
Water Filter (2).....	6" – 24" diameter

CYCLES OF OPERATION

Cycle	Softener		Filter	
	Range of time in minutes			
1. Backwash 1 st (upflow)	1-95.....		Backwash	1-95
2. Regenerate Draw/Slow Rinse (downflow or upflow).....	1-180			
3. Backwash 2 nd (upflow).....	1-95.....		Rinse	1-95
4. Fast Rinse (downflow)	1-95			
5. Regenerant Refill (in service with treated water).....	0.1-99.0			
6. Service (downflow)				

When replacing batteries follow state or local regulations for recycling and disposal.

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentration of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Acquired by use of external drain line flow control
2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area